## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-156967

(43)Date of publication of application : 17.06.1997

(51)Int.Cl.

CO3C 27/12 B32B 17/10 G10K 11/162 G10K 11/16

(21)Application number: 07-322915

(71)Applicant: SEKISUI CHEM CO LTD

(22)Date of filing:

12.12.1995

(72)Inventor: MIYAI JIRO

## (54) INTERLAYER FOR SOUND INSULATING LAMINATED GLASS AND SOUND INSULATING **LAMINATED GLASS**

## (57)Abstract:

PROBLEM TO BE SOLVED: To provide an interlayer for a sound insulating laminated glass, having a small optical strain and excellent in sound insulating properties and also provide the sound insulating laminated glass using the interlayer.

SOLUTION: This interlayer for a sound insulating laminated glass is a laminated resin film of at least two layers comprising two kinds of plasticized polyvinyl acetal resin films A and B. The resin film A comprises a polyvinyl acetal resin, prepared by acetalizing polyvinyl alcohol with a 4-6C aldehyde and having 8-30mol% vinyl acetate component content and a plasticizer. The resin film B comprises a polyvinyl acetal resin, obtained by acetalizing the polyvinyl alcohol with a 3C or a 4C aldehyde and having ≤4mol% vinyl acetate component content and a plasticizer. The total film thickness of the resin film A is >25 and ≤55% based on the film thickness of the laminated resin film and ≥0.10mm. The objective laminated glass is obtained by using the resultant interlayer.

## **LEGAL STATUS**

[Date of request for examination]

06.05.1999

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or

application converted registration]

[Date of final disposal for application]

[Patent number] [Date of registration] 3204890

29.06.2001

[Number of appeal against examiner's decision

of rejection]

[Date of requesting appeal against examiner's

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office